

# Product fiche

Delegated Regulation (EU) 1254/2014

Supplier name or trademark	<b>Flexit</b>
Model identifier	<b>Muto 100</b>
Specific energy consumption (cold zone)	<b>89,0 kWh/(m<sup>2</sup> x a)</b>
Specific energy consumption class (average zone)	<b>A+</b>
Specific energy consumption (average zone)	<b>-43,8 kWh/(m<sup>2</sup> x a)</b>
Specific energy consumption (warm zone)	<b>18,7 kWh/(m<sup>2</sup> x a)</b>
Typology	<b>Bidirectional Ventilation Unit (BVU)</b>
Type of drive	<b>Variable speed drive</b>
Type of heat recovery system	<b>Regenerative</b>
Thermal efficiency of heat recovery	<b>89,0 %</b>
Maximum flow rate	<b>38 m<sup>3</sup>/h</b>
Electric power input of the fan drive	<b>5,2 W</b>
Sound power level	<b>53 dB</b>
Reference flow rate	<b>35,000 m<sup>3</sup>/s</b>
Reference pressure difference	<b>10 Pa</b>
Specific Power Input	<b>0,15 W/(m<sup>3</sup>/h)</b>
Control factor	<b>0,65</b>
Control typology	<b>Local demand control - 0,65</b>
Maximum internal leakage rates	<b>- %</b>
Maximum external leakage rates	<b>- %</b>
Carry over	<b>0,0 %</b>
Position of visual filter warning	<b>LED indicator on the indoor unit</b>
Description of visual filter warning	<b>The filter indicator lights up at set intervals, 90, 180 or 365 days,</b>
Pre-/dis-assembly instructions URL	<b><a href="https://www.flexit.no/produkter/romventilator/romventilator_muto/romventilator_muto_160/">https://www.flexit.no/produkter/romventilator/romventilator_muto/romventilator_muto_160/</a></b>
Airflow sensitivity to pressure variations at + 20 Pa and - 20 Pa	<b>0,5 %</b>
Indoor/Outdoor air tightness	<b>0,1 m<sup>3</sup>/h</b>
Annual Electricity Consumption	<b>107,0 kWh electricity/annum</b>
Annual Heating Saved at cold climate	<b>9 141,0 kWh primary energy/annum</b>
Annual Heating Saved at average climate	<b>4 650,0 kWh primary energy/annum</b>
Annual Heating Saved at warm climate	<b>2 113,0 kWh primary energy/annum</b>