

# Facet Kitchen hoods and kitchen fans



New!



## Facet – new series of kitchen hoods and kitchen fans

Facet is a new series of kitchen hoods (E/F/S) and kitchen fans (M). Besides the narrower design, the series includes a number of improvements. Available in variants for connection to the ventilation system, for central ventilation, for an external extract air fan or with an integrated motor. Some models also have a built-in stove guard.

The series has several different advantages:

- Discreet installation with a height of only 60 mm
- Electronic control and settings
- LED light
- Metal grease filter, which can be washed in a dishwasher
- Electronic sliding damper in zinc on E/F/S models
- The kitchen fan (M) has an airflow-operated damper in steel
- Simpler installation and easier accessibility for maintenance
- Smaller amounts of plastic parts

## Models

Art. no.	Name	Model	Colour
118689	Kitchen hood Facet-E/F White	Unit/central ventilation	White
118690	Kitchen hood Facet-E/F RF	Unit/central ventilation	Stainless steel
118691	Kitchen hood Facet-S White	External exhaust fan	White
118692	Kitchen hood Facet-S RF	External exhaust fan	Stainless steel
118693	Kitchen fan Facet-M White	Integrated motor/fan	White
118694	Kitchen fan Facet-M RF	Integrated motor/fan	Stainless steel
118695	Kitchen hood Facet-E/F SV White	Unit/central ventilation + stove guard	White
118696	Kitchen hood Facet-E/F SV RF	Unit/central ventilation + stove guard	Stainless steel
118697	Circuit breaker unit SV230V 1x25A	For kitchen hood with stove guard	
118699*	Circuit breaker unit SV230V 3x16A	For kitchen hood with stove guard	

\* 400V power supply with star connection on 118699.



## Facet - E/F/S



Facet E/F/S kitchen hoods are designed for installation under wall cabinets, and connection to a ventilation unit or to central ventilation (E/F) or to an external extract air fan (S). Odour reduction is excellent. Fitted with a metal grease filter which can be cleaned in a dishwasher. Electronic sliding damper in metal, for easy adjustment of the forced air quantity and basic ventilation.

Electronic panel and good LED lighting with a very long lifetime.

Supplied with a 230V earthed cable and plug. E and F models supplied with a cable for power current to the ventilation unit.

S models are supplied with a cable and special switch for the external extract air fan. The hood is easy to install and maintain. A minimum installation height of 44 cm is required between an electric stove and the lower side of the kitchen fan.

For a gas stove the height must be increased to minimum 65 cm.

Can also be supplied as E or F models with an integrated stove guard (article no. 118695, 118696).

- Electronic sliding damper in metal
- Washable metal grease filter
- LED lighting
- Easy installation and adjustment
- Easy cleaning
- Excellent odour reduction

Technical data	
Height	60 mm
Height with volume section	130 mm
Width	599 mm
Depth	543 mm
Filter	Metal
Duct connection	Ø125 mm
Min. installation height (stove/gas stove)	44/65 cm
Lighting	LED 6.5W
Brightness	684 lux
Effective output	7 W
Rated voltage/frequency	230 V / 50 Hz
Odour removal capacity*	75% at 50 l/s
Socket	EU
Damper	Electronic sliding damper zinc
Control panel	Electronic

\* Odour-removing capacity according to SS-EN 13141-3:2017. Tested at an installed height of 60 cm above the stove.

## Facet - M



The Facet M kitchen fan is design for installation under wall cabinets and gives excellent odour reduction. Fitted with a metal grease filter which can be cleaned in a dishwasher. The fan has metal dampers, an electronic panel and good LED lighting with a very long lifetime.

Supplied with a 230V earthed cable. The hood is easy to install and is designed on "easy clean" principles for simple maintenance.

The motor unit can easily be taken out for cleaning. A minimum installation height of 44 cm is required between an electric stove and the lower side of the kitchen fan.

For a gas stove the height must be increased to minimum 65 cm.

- Excellent odour reduction
- Washable metal grease filter
- LED lighting
- Electronic control panel
- Energy-efficient EC motor

Technical data	
Height	60 mm
Width	599 mm
Depth	491 mm
Filter	Metal
Duct connection	Ø125 mm
Min. installation height (stove/gas stove)	44/65 cm
Lighting	LED 6.5 W
Brightness	684 lux
Speed	5
Free-blowing air quantity	29 - 92 l/s
Sound pressure	38 - 64 dB(A)
Sound effect	42 - 68 dB(A)
Rated voltage/frequency	230 V / 50 Hz
Effective output	80 W
Motor	EC
Odour removal capacity*	98%
Energy class	A+
Socket	EU
Damper	Steel airstream-operated damper
Control panel	Electronic

\* Odour-removing capacity according to SS-EN IEC 61591:2020.



Flexit supplies systems for a better indoor climate. Flexit is a market leader in residential ventilation and has provided ventilation systems to homes for over 40 years. Our systems are specially designed to improve the indoor climate in houses, in demanding conditions. So you can rest easy!

### Contact information

Tel.: +46 (0)10-209 86 01  
export@flexit.com

Follow us on

